

# Indoor Ambience Monitoring Sensor

Featuring LoRaWAN®

## AM300 Series



### ◆ Introduction

AM300 series is a compact indoor ambience monitoring sensor for measurement of temperature, humidity, light, CO<sub>2</sub> concentration, HCHO/O<sub>3</sub> level, TVOC, barometric pressure, PM2.5, PM10 and motion. The data will be shown on the E-ink screen in real-time, which helps to measure the indoor environment and comfort. AM300 series is widely used for offices, stores, classrooms, hospitals, etc.

Sensor data is transmitted using LoRaWAN® technology. Combining Milesight LoRaWAN® gateway and Milesight IoT Cloud, users can manage all sensor data remotely and visually.

### ◆ Features

- Integrated with multiple sensors like humidity, temperature, CO<sub>2</sub>, light, barometric pressure, PM2.5, PM10, etc.
- Multiple display modes and clear emoticon to easily understand the comfort levels via screen
- Support batteries or DC power supply
- Equipped with traffic light indicator and buzzer to indicate device status and threshold alarms
- Store locally 18,000 historical records and support retransmission to prevent data loss
- Compliant with standard LoRaWAN® gateways and network servers
- Quick and easy management with Milesight IoT Cloud

## ◆ Specifications

Model	AM307	AM308	AM319
<b>Wireless Transmission</b>			
Technology	LoRaWAN®		
Frequency	CN470/RU864/IN865/EU868/US915/AU915/KR920/AS923-1&2&3&4		
Tx Power	16dBm(868MHz)/22dBm(915MHz)/19dBm(470MHz)		
Sensitivity	-137dBm @300bps		
Work Mode	OTAA/ABP Class A	OTAA/ABP Class A	OTAA/ABP Class C
<b>Sensors</b>			
<b>Temperature</b>			
Operating Principle	Digital CMOSens® technology (MEMS)		
Range	-20°C - 60°C		
Accuracy <sup>1</sup>	± 0.2°C		
Resolution	0.1°C		
<b>Humidity</b>			
Operating Principle	Digital CMOSens® technology (MEMS)		
Range	0% - 100% RH		
Accuracy	± 2% RH		
Resolution	0.5% RH		
<b>Motion</b>			
Operating Principle	Passive infrared (PIR)		
Detection Range	80 ° Horizontal, 55 ° Vertical, 5m		
Status	Vacant/Occupied		
<b>Light</b>			
Operating Principle	Photodiode		
Range	0-60000 Lux (Determine as 6 levels, 0-5)		
<b>TVOC</b>			
Operating Principle	MOX (MEMS)		
Range <sup>1</sup>	1.00 - 5.00 (IAQ Rating)		
Accuracy	±1		
Resolution	0.01		
<b>Barometric Pressure</b>			
Operating Principle	Piezoresistive absolute pressure sensor (MEMS)		
Range	260 - 1260 hPa		

Accuracy	±0.5 hPa		
Resolution	0.1 hPa		
<b>Carbon Dioxide (CO<sub>2</sub>)</b>			
Operating Principle	Nondispersive Infrared (NDIR)		Photoacoustic
Range	400 - 5000 ppm		400 - 2000 ppm
Accuracy	± (30 ppm + 3 % of reading) (0°C to +50°C)		± (50 ppm + 5 % of reading) (-10°C to +60°C)
Resolution	1 ppm		1 ppm
<b>PM2.5 &amp; PM10</b>			
Operating Principle	—		Laser Scattering
Range	—		0 - 1000 µg/m <sup>3</sup>
Accuracy	—		0-100(±10µg/m <sup>3</sup> ), 100-1000(±10 %) (-10°C to +60°C)
Resolution	—		1 µg/m <sup>3</sup>
<b>Formaldehyde (HCHO)<sup>2</sup></b>			
Operating Principle	—		Electrochemical
Range <sup>3</sup>	—		0 - 1.25 mg/m <sup>3</sup>
Accuracy	—		±10 %
Resolution	—		0.01 mg/m <sup>3</sup>
Working Life	6 Years		
<b>Ozone (O<sub>3</sub>)<sup>2</sup></b>			
Operating Principle	—		Electrochemical
Range	—		0 - 10 ppm
Accuracy	—		±5 % FS
Resolution	—		0.01 ppm
Working Life	2 Years		
<b>Display &amp; Configuration</b>			
Display	4.2-inch Black & White E-Ink Screen		
Button	1 × Power Button + 1 × Reset Button		
LED & Buzzer	1 × Traffic Light Status Indicator + 1 × Buzzer		
Configuration	1. Mobile App via NFC 2. PC software via NFC or USB Type-C port		
<b>Physical Characteristics</b>			
Power Supply	1. 4 × 2700 mAh ER14505 Li-SOCl <sub>2</sub> Replaceable Batteries		5V/1A by Type-C Port

2. 5V/1A by Type-C Port			
Battery Life <sup>4</sup> (10 min interval)	Around 3 Years	Over 1 Year	—
Operating Temperature	-20°C - 60°C (E-Ink Screen: 0°C - 40°C)		
Relative Humidity	10% - 90% (non-condensing)		
Ingress Protection	IP30		
Dimension	100.8 × 114 × 22 mm (3.97 × 4.49 × 0.87 in)		
Installation	3M Tape Mounting, Wall Screw Mounting, 86 Box Mounting		
<b>Approvals</b>			
Regulatory	CE, FCC		
Environmental	RoHS		

**Note:**

1. Reference to IAQ rating guideline (conversion from mg/m<sup>3</sup> to ppm by the factor is about 0.5):

IAQ Rating	TVOC (mg/m <sup>3</sup> )	Air Quality
≤1.99	<0.3	Very Good
2.00 to 2.99	0.3 to 1.0	Good
3.00 to 3.99	1.0 to 3.0	Medium (not recommended for exposure > 12 months)
4.00 to 4.99	3.0 to 10.0	Poor (not recommended for exposure > 1 months)
≥5.00	>10.0	Bad (not recommended)

2. HCHO or O<sub>3</sub> sensor is alternative option and both support replacement.

3. For HCHO at 760 mmHg and 20°C, 1 ppm = 1.25 mg/m<sup>3</sup>.

4. The battery life is tested under laboratory conditions and for guideline purposes only.



WELKO Av. Providencia 2330, Of. 63  
+56 9 3174 3870 / +56 9 3427 0017  
ventas@welko.cl - www.welko.cl

