

Soil Conductivity Sensor

Milesight

Featuring LoRaWAN®

EM500-SMTC



EM500-SMTC is designed for measuring soil moisture, temperature and electrical conductivity in harsh environments and transmitting data using LoRaWAN® technology. With this low power consumption technology, EM500-SMTC can work up to 10 years with 19000 mAh battery. Combining with Milesight LoRaWAN® gateway and Milesight IoT Cloud solution, users can manage all sensor data remotely and visually.

EM500-SMTC is widely used for outdoor applications like smart agriculture, smart horticulture, etc.

Features

- High precision for multiple kinds of soil
- Corrosion resistance and tough probe
- Ultra-wide-distance transmission up to line of sight of 10km
- ➤ IP67 waterproof enclosure for harsh environment applications
- Built-in 19000 mAh replaceable battery and work for 10 years without replacement
- > Equipped with NFC for easy configuration
- Compliant with standard LoRaWAN® gateways and network servers
- > Quick and easy management with Milesight IoT Cloud solution

Applications

- > Irrigation Control
- > Greenhouse control
- Smart agriculture
- Smart horticulture
- Golf course maintenance



Wireless Transmission		
Technology	LoRaWAN [®]	
Frequency	CN470/IN865/RU864/EU868/US915/AU915/KR920/AS923	
Tx Power	16dBm(868)/20dBm(915)/19dBm(470)	
Sensitivity	-137dBm @300bps	
Mode	OTAA/ABP Class A	
Measurement		
Moisture		
Range	0% ~ 100% RH	
Accuracy	±2%(0~50%), ±3%(50%~100%)	
Resolution	0.01%	
Temperature		
Range	-40°C ~ 80°C	
Accuracy	±0.5°C	
Resolution	0.1°C	
Conductivity		
Range	0~20000 μs/cm	
Accuracy	±3%(0~10000 μs/cm), ±5%(10000~20000 μs/cm)	
Resolution	1 μs/cm	
Operation		
Power On & Off	NFC, Power Button (Internal)	
Configuration	Mobile App(via NFC) or PC Software(via USB Type-C)	
Physical Characteristics	S	
Cable Length	2 m	
Power Supply	19000 mAh Li-SOCL ₂ battery (ER34615)	
Battery Life*	10 years (10 min interval)	
Operating Temperature	-30°C to +70°C	
Relative Humidity	0% to 100% (non-condensing)	
Ingress Protection	IP67 (Transceiver)/IP68(Soil Sensor)	
	Transceiver: 105.4 × 71 × 69.5 mm (4.1 × 2.8 × 2.7 in)	
Dimension	Soil Sensor: 88 × 68 × 26 mm (3.5 × 2.7 × 1.0 in)	
	(Probe length: 50mm/1.97 in)	
Installation	Pole, wall or DIN Rail Mounting	

Approvals		
	Regulatory	CE, FCC, RoHS

^{*} Tested under laboratory conditions and for guideline purposes only.



WELKO Av. Providencia 2330, Of. 63

Xiamen Milesight IoT Co., Ltd. | www.milesight-iot.com









